

Pump piPREMIUM600 Si32-3x24

Item number: 02.01.124



- COAX® patented technology
- Side mounted for low building heights
- High vacuum flow
- Compact size and low weight
- Low noise level
- Modular design


Technical data

Description	Unit	Value
Material	-	Al. Nitrile (NBR). PA. PP. SS
Temperature, max.	°F	140
Temperature, min.	°F	32
Weight, min.	oz	562.5
Feed pressure, max.	psi	102
Noise level, max.	dBA	77
Noise level, min.	dBA	69
Feed pressure, optimum, max.	psi	87
Feed pressure, optimum, min.	psi	58
Vacuum, max.	-inHg	22.15
Vacuum, min.	-kPa	203.18

Performance

Ejector specification	Feed pressure psi	Air consumption scfm	Vacuum flow (scfm) at different vacuum levels (-inHg)								Max vacuum -inHg
			0	2	5	8	11	14	17	20	
piPREMIUM600	58.015	63.57	254.27	148.32	97.47	61.45	40.68	20.34	5.085		≥17.72
piPREMIUM600	72.52	76.28	290.29	167.39	112.3	72.043	43.23	31.57	17.8	9.11	≥20.67
piPREMIUM600	87.023	88.99	305.12	177.99	131.37	86.87	45.77	30.51	25.43	17.8	≥22.15

Dimensional drawings



Values specified in this datasheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Compressed air quality, DIN ISO 8573-1 class 4.

Tolerance and accuracy:

- Feed pressure tolerance ±0.02 MPa [2.9 psi]
- Vacuum flow/evacuation time accuracy ±10%.

Accessories

- 01.04.040 | Sanitary Gasket for 3" EPDM
- 01.04.044 | Quick Clamp 3" for TC
- 01.04.491 | Regulator kit 1" 600-800
- 02.01.025 | Wall mounting kit pump piPREMIUM 600-800
- 02.01.649 | Maintenance kit piFLOW® pumps