


piBASIC 400 with central exhaust Si32-3 x 16

Item number: 02.07.814



- COAX® patented technology
- Side mounted for low building heights
- High vacuum flow
- Compact size and low weight
- Modular design

Technical data

Description	Unit	Value
Material	-	Al. Cu. CuZn. NBR (FKM). PA. POM. SS. Zn
Temperature, max.	°F	140
Temperature, min.	°F	32
Weight, min.	oz	411.88
Feed pressure, max.	psi	102
Noise level, max.	dBA	69
Feed pressure, optimum, max.	psi	87
Feed pressure, optimum, min.	psi	58
Vacuum, max.	-inHg	19.19
Vacuum, min.	-kPa	253.98
Noise level, reduction	dBA	77

Performance

Ejector specification	Feed pressure psi	Air consumption scfm	Vacuum flow (scfm) at different vacuum levels (-inHg)								Max vacuum -inHg
			0	2	5	8	11	14	17	20	
piBASIC400	58.015	42.38	144.085	91.11	63.57	40.68	27.12	13.56	3.39		≥17.72
piBASIC400	72.52	50.85	165.27	101.71	74.16	47.46	28.82	20.98	11.87	6.14	≥20.67
piBASIC400	87.023	59.33	173.75	108.064	88.99	57.21	30.51	20.34	16.95	11.87	≥22.15

