

Vane pump 200 IE3 460V, 208V,230V

Item number: 02.09.780



- Electro mechanical generated vacuum
-
- High vacuum flow
-
- Integrated inlet filter and control valves
-
- Oil-free
-
- Vibration stable


Technical data

Description	Unit	Value
Material	-	Iron FE
Weight, max.	oz	5375
Electric connection	-	3AC 460V 60Hz. 3AC 208V 60Hz. 3AC 230V 60Hz
Noise level, max.	dBA	75
Rated Power (60Hz)	hp	0.004

Performance

Ejector specification	Feed pressure psi	Air consumption scfm	Vacuum flow (scfm) at different vacuum levels (-inHg)									Max vacuum -inHg
			0	2	5	8	11	14	17	20	26	
Vane pump 200 60Hz			46.19	41.11	36.021	30.72	25.64	20.55	15.47	10.17	5.085	≥26.58

Dimensional drawings



Values specified in this datasheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Compressed air quality, DIN ISO 8573-1 class 4.

Tolerance and accuracy:

- Feed pressure tolerance ±0.02 MPa [2.9 psi]
- Vacuum flow/evacuation time accuracy ±10%.

Accessories

- 02.05.864 | Hose connection kit 200
- 02.05.949 | Hose connection kit G1" - D=63