

## Suction cup OBF65x170P Polyurethane 55/60, M10x1.5 male

Item number: OBF65x170P.5R.M10M



- Special designed friction cups for oily surfaces, such as sheets in metal forming processes.
- Normal wear on friction cup will not affect the long term shear force performance.
- Best choice if > 0,1g/m2 press oil is used on the sheet.
- Thanks to the strong grip on oily surfaces, the suction cups can withstand high shear forces, typically 2–4 times more than corresponding conventional suction cups.
- The "OBF" design is suitable for oblong objects with domed and flat surfaces, such as those encountered with body parts in the automotive industry.
- Can handle objects with height differences.
- Fitting option, male G3/8", with a swivel function prior to the locking operation, for easy positioning of the oval cup.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

### Technical data

Description	Unit	Value
Suction cup shape	-	Bellows
Application	-	Oily sheet metal
Suction cup design	-	Oval
Characteristics	-	Oily sheet metal
Material	-	Polyurethane (PU)
Weight, max.	oz	10.93
Weight, min.	oz	10.19
Suction cup model	-	OBF
Volume	in <sup>3</sup>	12.20
Length	in	7.36
Fitting size	-	M10x1.5
Fitting option	-	None
Fitting style	-	Male
Fitting type	-	M-thread
Width (1)	in	3.23
Suction cup model	-	OBF65x170P Dry metal sheet
Movement, vertical max.	in	0.59
Curve radius, min.	in	1.97
Suction cup model	-	OBF65x170P Oily steel plate
Movement, vertical max.	in	0.59
Curve radius, min.	in	1.97

## Performance - Lifting forces

	Vertical (lb)	Parallel (lb)
OBF65x170P Dry metal sheet		
17.72 -inHg	107.68	102.51
26.58 -inHg	143.65	156.47
OBF65x170P Oily steel plate		
17.72 -inHg	94.20	80.032
26.58 -inHg	132.19	119.37


## Material

Name	Polyurethane (PU55)	Polyurethane (PU60)
Color	Orange	Green transparent
Temperature, min.   °F	50.0	50.0
Temperature max.   °F	122.0	122.0
Hardness   °Shore A	55	60

## Material resistance

Alcohol	n/a	n/a
Concentrated acids	Fair	Fair
Ethanol	Fair	Fair
Hydrolysis	Fair	Fair
Methanol	Poor	Poor
Oil	Excellent	Excellent
Oxidation	Poor	Poor
Gasoline	Fair	Fair
Wear resistance	Excellent	Excellent
Weather and ozone	Excellent	Excellent

## Dimensional drawings



**Values specified in this data sheet are tested at (unless otherwise stated):**

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.