

Plastic Fiber-Optic Cable

Reflex Mode

FRH01-2M-10HF

Part Number



- Especially suitable in applications where only minimal space is available
- Fiber-optic cable can be cut to length by the cutting tool

Technical Data


Optical Data

Fiber Core Diameter	1 mm
Fiber	Step Index
Fiber Distribution	parallel arrangement
Detection range with P1XD0xx	100 mm
Detection range P1XD10x/11x	130 mm
Detection range P1XD12x/13x	100 mm
Detection range P1XD2xx red light	140 mm
Detection range P1XD2xx blue light	100 mm
Detection range P1XD2xx pink light	170 mm
Opening Angle	55 °


Mechanical Data

Cable type	High-flex
Temperature Range	-40...60 °C
Bending Radius	2 mm
Fiber-Optic Length L	2 m
Jacket Material	Plastic, PE
Fiber Optic Material	Plastic, PMMA
End sleeve shape	Hexagonal
Material End Sleeve	Stainless steel, V2A (1.4305/303)
Jacket Diameter	2,2 mm
Light Emission	sidewise
End Sleeve No.	FRH01
Packaging unit	1 Piece
Scope of delivery	1 × fiber-optic cable
	1 × M4 hex nut
	1 × Z0015 cutting tool

Plastic fiber-optic cables are very flexible and suitable for use in confined spaces. The fiber optics are supplied in 2 m lengths. Special lengths of up to 50 m are possible. Users can shorten the fiber optics using the Z0015 cutting tool.



FRH01-2M-10HF



All dimensions in mm (1 mm = 0.03937 Inch)

