

Plastic Fiber-Optic Cable

Through-Beam Mode

FTF02-2M-10

Part Number



- Especially suitable in applications where only minimal space is available
- Fiber-optic cable can be cut to length by the cutting tool

Technical Data

Optical Data

Fiber Core Diameter	1 mm
Fiber	Step Index
Fiber Distribution	parallel arrangement
Range with P1XD0xx	240 mm
Range P1XD10x/11x	320 mm
Range P1XD12x/13x	300 mm
Range P1XD2xx red light	270 mm
Range P1XD2xx blue light	330 mm
Range P1XD2xx pink light	370 mm
Opening Angle	55 °

Mechanical Data

Cable type	Standard
Temperature Range	-40...70 °C
Bending Radius	20 mm
Fiber-Optic Length L	2 m
Jacket Material	Plastic, PE
Fiber Optic Material	Plastic, PMMA
Material End Sleeve	Stainless steel, V2A (1.4305/303)
End sleeve shape	Flat
Jacket Diameter	2,2 mm
Light Emission	sidewise
End Sleeve No.	FTF02
Packaging unit	2 Pieces
Scope of delivery	1 × Z0015 cutting tool 2 × BEF-SET-23 mounting sets 2 × fiber-optic cables

Plastic fiber-optic cables are very flexible and suitable for use in confined spaces. The fiber optics are supplied in 2 m lengths. Special lengths of up to 50 m are possible. Users can shorten the fiber optics using the Z0015 cutting tool.



